



NOTES  
 PROVIDE WALL BRACING AT ALL CORNERS AND 25' O.C. - BRACING TO BE 1/16" OSB  
 PROVIDE FIREBLOCKING AT 0'-0" WHERE NEEDED  
 PROVIDE 2" RV33 ROOF VENTS ON REAR SIDE OF GARAGE DOWN 3' FROM PEAK  
 ALL EXTERIOR HOSE BIBS TO HAVE APPROVED BACKFLOW PREVENTION DEVICES  
 ALL 2X4 STUDS TO BE 5-DRY\* #6 HEM FIR OR BETTER  
 ALL 2X4 R/L TO BE #2 HEM FIR OR BETTER  
 ALL 2X10 TO BE #2 DOUG FIR 4 BETTER  
 STAIRS TO HAVE MIN. 6'-8" HEADROOM AT NOSE OF TREAD  
 ALL EXT HEADERS TO BE 2-2X10 #2 4 BTR UNLESS NOTED OTHERWISE

BILL MOST CONSTRUCTION, INC.  
 P.O. BOX 789  
 BROOMFIELD CO 80038  
 303-280-0935

**MAIN FLOOR LAYOUT**  
 SCALE: 1/4" = 1'-0"  
 1852 SQ. FT.